





























PREMISES CENTRAL OFFICE CABLES

OUT-DISTANCING INTERCONNECTED TRANSMISSIONS

www.superioressexcommunications.com

CABLE	PRODUCT NUMBER	PRODUCT NAME	CONDUCTOR TYPE	INSULATION	PAIR COUNT	AWG	INSULATION COLOR	LISTING	APPLICATIONS	PACKAGING
-------	----------------	--------------	----------------	------------	------------	-----	------------------	---------	--------------	-----------

	12-201-15	Heavy Duty Distribution Frame Wire (HD-DFW)	Tinned copper	Heavy duty, abrasion resistant PVC	1	22	White/Blue	CMR	High stress use	3,000' Parallel Cone	
	12-403-13	Distribution Frame Wire (DFW)		Semi-rigid PVC				White/Blue	CM	Normal use	1,000' Spool
	12-305-13						Black/White				
	12-313-13						White/Blue	3,280' Parallel Cone			
	12-103-13										
	12-101-13						White/Red				
	12-109-13						Yellow/Blue				
	02-002-13	Indoor/Outdoor Cross-Connect Wire (XCW)		Solid bare copper			Flame retardant PVC insulated conductor	24	N/A	1,000' Spool	
	02-001-13		White/Blue								
	02-050-13		White/Orange								
	02-051-13		White/Green								
	02-006-13		White/Red								
	02-011-23		Cross-Connect Category 5 Wire (XCW)		White/Blue						

CABLE	PRODUCT NUMBER	PRODUCT NAME	CONDUCTOR TYPE	INSULATION	PAIR COUNT	AWG	JACKET	LISTING	APPLICATIONS	PACKAGING						
	55-399-38	600C Series	Tinned copper	Polyolefin	6	22	Gray PVC	CMR	<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C • DS2 	10,000' Reel						
	55-799-38				25					PVC	25	24	CMR	<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C 	5,000' Reel	
	02-815-10	Switchboard 85 and Shielded Switchboard 85 (SWBD)		32	25	24			CMR							<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C
	02-832-10			32						25	24	CMR	<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C 	5,000' Reel		
	02-097-61	Switchboard 85 and Shielded Switchboard 85 (SSWBD)		25	25	24			CMR						<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C • DS2 	5,000' Reel
	02-098-61			32						25	24	CMR	<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C • DS2 	5,000' Reel		
	55-799-21	1161A Series Category 3		25	25	24			CMR						<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C • DS2 	5,000' Reel
	55-899-21			28						25	24	CMR	<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C • DS2 	5,000' Reel		
	55-A99-21			32												
	55-021-23	Switchboard 100 Ohm		2	25	24			CMR	<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C • 4 Mbps token ring (IEEE 802.5) • 10 Mbps 10BASE-T Ethernet (IEEE 802.3) 	Master Reel					
	55-299-23			4								25	24	CMR	<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C • 4 Mbps token ring (IEEE 802.5) • 10 Mbps 10BASE-T Ethernet (IEEE 802.3) 	Master Reel
	55-A99-47	Switchboard 100 Ohm (200A/800A Series (Canadian Color Code))		33	25	24			CMR	<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C 	2,000' Reel					
	55-899-43	T100 Series		28								24	CMR	<ul style="list-style-type: none"> • T1/DS1 • T1C/DS1C 	5,000' Reel	



www.superioressexcommunications.com